

SUNNY TRIPOWER

15000TL / 20000TL / 25000TL



STP 15000TL-30 / STP 20000TL-30 / STP 25000TL-30



SMA ShadeFix
STRING LEVEL OPTIMIZATION

Efficient

- Maximum efficiency of 98.4%
- Yield increase without installation effort due to integrated shade management SMA ShadeFix

Safe

- DC surge arrester (SPD type II) can be integrated

Flexible

- DC input voltage of up to 1000 V
- Multistring capability for optimum system design
- Optional display

Innovative

- Cutting-edge grid management functions with Integrated Plant Control
- Reactive power available 24/7 (Q on Demand 24/7)

SUNNY TRIPOWER

15000TL / 20000TL / 25000TL

The versatile specialist for large-scale commercial plants and solar power plants

The Sunny Tripower is the ideal inverter for large-scale commercial and industrial plants. Not only does it deliver extraordinary high yields with an efficiency of 98.4%, but it also offers enormous design flexibility and compatibility with many PV modules thanks to its multistring capabilities and wide input voltage range.


The future is now: the Sunny Tripower comes with cutting-edge grid management functions such as Integrated Plant Control, which allows the inverter to regulate reactive power at the point of common coupling. Separate controllers are no longer needed, lowering system costs. Another new feature—reactive power provision on demand (Q on Demand 24/7).

SUNNY TRIPOWER





15000TL / 20000TL / 25000TL

Technical Data	Sunny Tripower 15000TL
Input (DC)	
Max. generator power	27000 Wp
DC rated power	15330 W
Max. input voltage	1000 V
MPP voltage range / rated input voltage	240 V to 800 V / 600 V
Min. input voltage / start input voltage	150 V / 188 V
Max. input current input A / input B	33 A / 33 A
Number of independent MPP inputs / strings per MPP input	2 / A:3; B:3
Output (AC)	
Rated power (at 230 V, 50 Hz)	15000 W
Max. AC apparent power	15000 VA
AC nominal voltage	3 / N / PE; 230 V / 400 V
AC grid frequency / range	50 Hz / 44 Hz to 55 Hz
Rated power frequency / rated grid voltage	50 Hz / 230 V
Max. output current / Rated output current	29 A / 21.7 A
Power factor at rated power / Adjustable displacement power factor	1 / 0 overexcited to 0 underexcited
THD	≤ 3%
Feed-in phases / connection phases	3 / 3
Efficiency	
Max. efficiency / European Efficiency	98.4% / 98.0%
Protective devices	
DC-side disconnection device	●
Ground fault monitoring / grid monitoring	● / ●
DC surge arrester (Type II) can be integrated	○
DC reverse polarity protection / AC short-circuit current capability / galvanically isolated	● / ● / -
All-pole sensitive residual-current monitoring unit	●
Protection class (according to IEC 62109-1) / overvoltage category (according to IEC 62109-1)	I / AC: III; DC: II
General data	
Dimensions (W / H / D)	661 / 682 / 264 mm (26.0 / 26.9 / 10.4 inch)
Weight	61 kg (134.48 lb)
Operating temperature range	-25 °C to +60 °C (-13 °F to +140 °F)
Noise emission (typical)	51 dB(A)
Self-consumption (at night)	1 W
Topology / cooling concept	Transformerless / Opticool
Degree of protection (as per IEC 60529)	IP65
Climatic category (according to IEC 60721-3-4)	4K4H
Maximum permissible value for relative humidity (non-condensing)	100%
Features / function / Accessories	
DC connection / AC connection	SUNCLIX / spring-cage terminal
Display	○
Interface: RS485, Speedwire/Webconnect	○ / ●
Data interface: SMA Modbus / SunSpec Modbus	● / ●
Multifunction relay / Power Control Module	○ / ○
Shade management SMA ShadeFix / Integrated Plant Control / Q on Demand 24/7	● / ● / ●
Off-Grid capable / SMA Fuel Save Controller compatible	● / ●
Guarantee: 5 / 10 / 15 / 20 years	● / ○ / ○ / ○
Certificates and permits (more available on request)	ANRE 30, AS 4777, BDEW 2008, C10/11:2012, CE, CEI 0-16, CEI 0-21, DEWA 2.0, EN 50438:2013*, G59/3, IEC 60068-2-x, IEC 61727, IEC 62109-1/2, IEC 62116, MEA 2013, NBR 16149, NEN EN 50438, NRS 097-2-1, PEA 2013, PPC, RD 1699/413, RD 661/2007, Res. n°7:2013, RfG compliant, SI4777, TOR D4, TR 3.2.2, UTE C15-712-1, VDE 0126-1-1, VDE-ARN 4105, VFR 2014
* Does not apply to all national appendices of EN 50438	
Type designation	STP 15000TL-30

Efficiency Curve



Accessory

-  RS485 interface DM-485CB-10
-  DC surge arrester Typ II, inputs A and B DCSPD KIT3-10
-  Multifunction relay MFR01-10
-  Power Control Module PWCMOD-10

● Standard features ○ Optional features – Not available
 Data at nominal conditions
 Status: 11/2019

Technical Data

Input (DC)

Max. generator power
DC rated power
Max. input voltage
MPP voltage range / rated input voltage
Min. input voltage / start input voltage
Max. input current input A / input B
Number of independent MPP inputs / strings per MPP input

Output (AC)

Rated power (at 230 V, 50 Hz)
Max. AC apparent power
AC nominal voltage
AC grid frequency / range
Rated power frequency / rated grid voltage
Max. output current / Rated output current
Power factor at rated power / Adjustable displacement power factor
THD
Feed-in phases / connection phases

Efficiency

Max. efficiency / European Efficiency

Protective devices

DC-side disconnection device
Ground fault monitoring / grid monitoring
DC surge arrester (Type II) can be integrated
DC reverse polarity protection / AC short-circuit current capability / galvanically isolated
All-pole sensitive residual-current monitoring unit
Protection class (according to IEC 62109-1) / overvoltage category (according to IEC 62109-1)

General data

Dimensions (W / H / D)
Weight
Operating temperature range
Noise emission (typical)
Self-consumption (at night)
Topology / cooling concept
Degree of protection (as per IEC 60529)
Climatic category (according to IEC 60721-3-4)
Maximum permissible value for relative humidity (non-condensing)

Features / function / Accessories

DC connection / AC connection
Display
Interface: RS485, Speedwire/Webconnect
Data interface: SMA Modbus / SunSpec Modbus
Multifunction relay / Power Control Module
Shade management SMA ShadeFix / Integrated Plant Control / Q on Demand 24/7
Off-Grid capable / SMA Fuel Save Controller compatible
Guarantee: 5 / 10 / 15 / 20 years
Certificates and permits (more available on request)

* Does not apply to all national appendices of EN 50438

Sunny Tripower 20000TL

36000 W _p
20440 W
1000 V
320 V to 800 V / 600 V
150 V / 188 V
33 A / 33 A
2 / A:3; B:3

Sunny Tripower 25000TL

45000 W _p
25550 W
1000 V
390 V to 800 V / 600 V
150 V / 188 V
33 A / 33 A
2 / A:3; B:3

20000 W
20000 VA
3 / N / PE; 230 V / 400 V
50 Hz / 44 Hz to 55 Hz
50 Hz / 230 V
29 A / 29 A
36.2 A / 36.2 A
1 / 0 overexcited to 0 underexcited
≤ 3%
3 / 3

98.4% / 98.0%
98.3% / 98.1%

●
● / ●
○
● / ● / -
●
I / AC: III; DC: II

661 / 682 / 264 mm (26.0 / 26.9 / 10.4 inch)
61 kg (134.48 lb)
-25 °C to +60 °C (-13 °F to +140 °F)
51 dB(A)
1 W
Transformerless / Opticool
IP65
4K4H
100%

SUNCLIX / spring-cage terminal
○
○ / ●
● / ●
○ / ○
● / ● / ●
● / ●
● / ○ / ○ / ○

ANRE 30, AS 4777, BDEW 2008, C10/11:2012, CE, CEI 0-16, CEI 0-21, DEWA 2.0, EN 50438:2013*, G59/3, IEC 60068-2-x, IEC 61727, IEC 62109-1/2, IEC 62116, MEA 2013, NBR 16149, NEN EN 50438, NRS 097-2-1, PEA 2013, PPC, RD 1699/413, RD 661/2007, Res. n°7:2013, RfG compliant, SI4777, TOR D4, TR 3.2.2, UTE C15-712-1, VDE 0126-1-1, VDE-AR-N 4105, VFR 2014

Type designation

STP 20000TL-30

STP 25000TL-30

www.SunnyPortal.com

Professional PV system monitoring, management and data display



www.SMA-Australia.com.au

SMA Solar Technology

STP152T130ALDS-040 SMA and Sunny Tripower are registered trademarks of SMA Solar Technology AG. SUNCLIX is a registered trademark of PHOENIX CONTACT GmbH & Co. KG. Printed on FSC paper. All products and services described and all technical data are subject to change, even for reasons of country-specific deviations, at any time without notice. SMA assumes no liability for typographical and other errors. For the latest information, please visit www.SMA-Solar.com.